

**TECHNICAL INFORMATION**

<b>BRICK NAME</b>	<b>CATEGORY 1 COMPRISING OF</b> Soft Red Reclamation Soft Red Soft Red Multi Weathered Soft Red Reclamation Weathered Soft Red Capital Blend Soft Red
<b>BRICK TYPE</b>	Through colour clay handmade brick
<b>SPECIFICATION</b>	Manufactured to BS EN 771-1:2011
<b>SIZE*</b>	68 x 228 x 108mm 57 x 228 x 108mm 65 x 215 x 102.5mm
<b>DIMENSIONAL TOLERANCE:</b>	T1
<b>RANGE:</b>	R1
<b>COMPRESSIVE STRENGTH</b>	Mean - 10.5 N/MM <sup>2</sup>
<b>WATER ABSORPTION</b>	Mean - 13%
<b>SOLUBLE SALT CLASSIFICATION</b>	S2
<b>BULK DENSITY</b>	1500 kg/m
<b>PACKAGING</b>	Shrink wrapped on wooden pallets in packs of 540 (68mm Imperial) 612 (57mm Imperial) 648 (65mm Metric)
<b>PACK SIZE; LxWxH</b>	1100 x 1100 x 1100mm Approx.
<b>PACK WEIGHT</b>	1.4 / 1.5 Tonnes Approx.
<b>USAGE</b>	Always mix from several packs, working vertically down the blades, not horizontally across the tops of the packs
<b>SAMPLES</b>	Samples will be supplied on request
<b>DURABILITY</b>	F2
<b>PERFORMANCE</b>	The recommendations of good practice made in the relevant British Standards regarding design and workmanship must be fully observed. Liability cannot be accepted for the performance of the product if used outside our recommendations. Guidance on the use of these bricks in specific situations is readily available from us.

\*Individual bricks may vary dimensionally; this is a natural characteristic of fired clay bricks and is catered for in the relevant European Standard.

