

DECLARATION OF PERFORMANCE

Category 9 comprising of
Pre War Common - Dual Faced
Tumbled Weathered Pre War Common
Outside Blend
Weathered Outside Blend
Tumbled Weathered Outside Blend



CAT 9 - PWC - 2015

Group HD, Category II

Intended use or uses of the construction product, in accordance with with applicable harmonised technical specification, as foreseen by the manufacturer: **Facing clay masonry unit for internal or external use, load bearing or non load bearing masonry structures**

ESSENTIAL CHARACTERISTICS	PERFORMANCE		HARMONISED TECHNICAL SPECIFICATION
Dimensional Tolerances mm	73 x 215 x 102.5		BS EN771-1
	65 x 215 x 102.5		
	Tolerance	T2	
Range	R2		
Compressive Strength (Standard shape, tested normal to the bed face of the unit) N/mm ²	Mean	44.8	
	Category	II	
Dimensional Stability N/mm ²	NPD		
Bond Strength Fixed value N/mm ²	NPD		
Active Soluble Salts	S2		
Reaction to Fire	A1		
Water Absorption %	22		BS EN771-1
Water Vapour Permeability	NPD		
Direct Airborne Sound Insulation kg/m ³ (gross)	NPD		
Thermal Properties	NPD		
Durability Against Freeze Thaw	F1		
Dangerous Substances	NPD		

The performance of the product(s) identified above is in conformity with the declared values

Signed for and on behalf of the manufacturer by:

Jason Hughes, Managing Director

March 2015

Imperial Bricks
Crowgreaves Farm
Stableford
Bridgnorth
Shropshire
WV15 5LT