DECLARATION OF PERFORMANCE

Category 47 comprising of Cheshire Pre War Weathered Cheshire Pre War Dark Weathered Cheshire Pre War





Group HD, Category II Clay Bricks

Intended use or uses of the construction product, in accordance with with applicable harmonised technical specification, as foreseen by the manufacturer: Facing clay masonry unit for internal or external use, load bearing or non load bearing masonry structures

ESSENTIAL CHARACTERISTICS	PERFORMANCE		HARMONISED TECHNICAL SPECIFICATION
Dimensional Tolerances mm	73 x 228 x 108 Weathered Cheshire Pre War Only 73 x 215 x 102.5 65 x 215 x 102.5 Weathered Cheshire Pre War Only		
	Tolerance	T1	BS EN771-1:2011
	Range	R1	
Compressive Strength (Standard shape, tested normal to the bed face of the unit) N/mm ²	Mean	41.4	
	Category	П	
Dimensional Stability N/mm²	NPD		
Bond Strength Fixed value N/mm ²	NPD		
Active Soluble Salts	S2		
Reaction to Fire	A1		Commission Decision 2000/605/EC
Water Absorption %	16		BS EN771-1:2011
Water Vapour Permeability	NPD		
Direct Airborne Sound Insulation kg/m³ (gross)	NPD		
Thermal Properties	NPD		
Durability Against Freeze Thaw	F2		
Dangerous Substances	NPD		

The performance of the product(s) identified above is in conformity with the declared values

Signed for and on behalf of the manufacturer by:

Jason Hughes, Managing Director

Collegher

June 2021

Crowgreaves Farm
Stableford
Bridgnorth
Shropshire

Imperial Bricks

Shropshire WV15 5LT