DECLARATION OF PERFORMANCE

Category 46 comprising of

Blue Brindle Brick Blue Brindle Paver Russet Paver Ochre Paver



CAT 46 - BB - 2021

Group HD, Category II Clay Bricks

Intended use or uses of the construction product, in accordance with with applicable harmonised technical specification, as foreseen by the manufacturer: Facing clay masonry unit for internal or external use, load bearing or non load bearing masonry structures

ESSENTIAL CHARACTERISTICS	PERFORMANCE		HARMONISED TECHNICAL SPECIFICATION
Dimensional Tolerances mm	73 x 225 x 102 50 x 200 x 100		
	Tolerance	T1	BS EN771-1:2011
	Range	R1	
Compressive Strength (Standard shape, tested normal to the bed face of the unit) N/mm²	Mean	92	
	Category	II	
Dimensional Stability N/mm²	NPD		
Bond Strength Fixed value N/mm ²	NPD		
Active Soluble Salts	\$2		
Reaction to Fire	A1		Commission Decision 2000/605/EC
Water Absorption %	7		- BS EN771-1:2011
Water Vapour Permeability	NPD		
Direct Airborne Sound Insulation kg/m³ (gross)	NPD		
Thermal Properties	NPD		
Durability Against Freeze Thaw	F2		
Dangerous Substances	NPD		

The performance of the product(s) identified above is in conformity with the declared values

Signed for and on behalf of the manufacturer by:

Jason Hughes, Managing Director

Conference

March 2021

Imperial Bricks

Crowgreaves Farm

Stableford

Bridgnorth

Shropshire

WV15 5LT