

DECLARATION OF PERFORMANCE

Category 9 comprising of
 Pre War Common
 Weathered Pre War Common
 Tumbled Weathered Pre War Common
 Outside Blend
 Weathered Outside Blend
 Tumbled Weathered Outside Blend



CAT 9 - PWC - 2015

Group HD, Category II

Intended use or uses of the construction product, in accordance with with applicable harmonised technical specification, as foreseen by the manufacturer: **Facing clay masonry unit for internal or external use, load bearing or non load bearing masonry structures**

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION	
Dimensional Tolerances mm	73 x 215 x 102.5	BS EN771-1	
	65 x 215 x 102.5		
	Tolerance		T2
Range	R2		
Compressive Strength (Standard shape, tested normal to the bed face of the unit) N/mm ²	Mean		44.8
	Category		II
Dimensional Stability N/mm ²	NPD		
Bond Strength Fixed value N/mm ²	NPD		
Active Soluble Salts	S2		
Reaction to Fire	A1		Commission Decision 2000/605/EC
Water Absorption %	22	BS EN771-1	
Water Vapour Permeability	NPD		
Direct Airborne Sound Insulation kg/m ³ (gross)	NPD		
Thermal Properties	NPD		
Durability Against Freeze Thaw	F1		
Dangerous Substances	NPD		

The performance of the product(s) identified above is in conformity with the declared values

Signed for and on behalf of the manufacturer by:

Jason Hughes, Managing Director

March 2015

Imperial Bricks
 Crowgreaves Farm
 Stableford
 Bridgnorth
 Shropshire
 WV15 5LT