

DECLARATION OF PERFORMANCE



No. 8.1.3
GROUP HD, CATEGORY II CLAY BRICKS

65mm Chatham Antique

Intended use or uses of the construction product, in accordance with with applicable harmonised technical specification, as foreseen by the manufacturer: Facing clay masonry unit for internal or external use, load bearing or non load bearing masonry structures

ESSENTIAL CHARACTERISTICS	PERFORMANCE		HARMONISED TECHNICAL SPECIFICATION
DIMENSIONAL TOLERANCES (mm)	65 x 215 x 102.5mm		BS EN771-1:2011
	TOLERANCE	T1	
	RANGE	R1	
COMPRESSION STRENGTH (Standard shape, tested normal to the bed face of the unit.) N/mm²	MEAN	20	
	CATEGORY	II	
DIMENSIONAL STABILITY	NPD		
BOND STRENGTH (Fixed Value N/mm²)	NPD		
ACTIVE SOLUBLE SALTS	S2		
REACTION TO FIRE	A1		COMMISSION DECISION 2000/605/EC
WATER ABSORPTION %	≤ 15		BS EN771-1:2011
WATER VAPOUR PERMEABILITY	NPD		
DIRECT AIRBOURNE SOUND INSULATION kg/mm³ (gross)	NPD		
THERMAL PROPERTIES	NPD		
DURABILITY AGAINST FREEZE THAW	F2		
DANGEROUS SUBSTANCES	NPD		

The performance of the product(s) identified above is in conformity with the declared values:

Signed for and on behalf of the manufacturer by:

Jason Hughes, Managing Director

January 2023

Imperial Bricks
Crowgreaves Farm
Stableford
Bridgnorth
Shropshire
WV15 5LT

