



WENTWORTH PAVER



PRODUCT CODE	MMWENT/PAVER/50
PRODUCT RANGE	Clay paving brick
CLASSIFICATION	PA - Paving Class A - Units that are selected or produced for their durability and for a high degree of uniformity in size and shape, and that have dimensions such that the ratio of work size length to work size width is approximately 1:1; 2:1 or 3:1.
SIZE	220 x 52 x 50mm
NIBBED	NO
CHAMFERED	YES
PAVERS PER M ²	82
COMPRESSIVE STRENGTH	>33MPa
AVERAGE MODULUS OF RUPTURE	>4MPa
AVERAGE MASS PER PAVER	1.2kg
PAVERS PER PALLET	1064
TYPICAL 24 HOUR WATER ABSORPTION	>7%
EXPOSURE ZONE SUITABILITY	1-3 Light Traffic
MOISTURE EXPANSION CATEGORY	Category II
PERFORMANCE	Variations in colour, texture and size are natural characteristics of clay products and production variations can occur from batch to batch. Whilst every effort is made to provide brochures consistent with products delivered to site, they should be viewed as a guide only.



For more information on products, services, advice and technical guidelines please contact our sales team.

01746 330994
sales@imperialbricks.co.uk
www.imperialbricks.co.uk

Individual bricks may vary dimensionally; this is a natural characteristic of fired clay bricks and is catered for in BS EN 771-1.
 Technical data correct at time of issue. Always order samples before purchasing and follow good practice guidelines.



Sedex Member



VERISIO LUCIDEON



UK
CA